



Model	1. 53 Circular Counter	1. 86 Circular Counter	2 Circular Counter	2.5 Circular Counter
Pixel Pitch	1.538mm	1.86mm	2mm	2.5mm
Pixel Density	422,500pixels/sqm	288,906pixels/sqm	250,000pixels/sqm	160,000pixels/sqm
Application	Indoor	Indoor	Indoor	Indoor
LED Configuration	GOB1212	SMD1515	SMD1515	SMD1515
Module Size	320*160mm	320*160mm	320*160mm	320*160mm
Module resolution	208*104dots	172*86dots	160*80dots	128*64dots
Shown Size	1280*800mm	1280*800mm	1280*800mm	1280*800mm
Cabinet Size	365*365*1280mm	365*365*1280mm	365*365*1280mm	365*365*1280mm
Display Resolution	832*520dots	688*430dots	640*400dots	512*320dots
Best Viewing distance	≥1.5m	≥1.8m	≥2m	≥2.5m
Brightness	600-800nits			
Refresh Rate	3840 Hz			
Best Viewing Angle	X:140° / Y:120°			
Working Voltage	AC200~240V (+/-10%)			
Maintenance Way	Front /Rear Maintence			
Power Consumption	<360W/m²			
Life Span	100,000Hours			