

Outdoor Rental LED Display MR Series

Flexible & Creative LED Display Solution

Designed for curved, irregular and custom-shaped installations, the MR Series combines high refresh performance, multiple pixel-pitch options and flexible rental-display architecture for stages, retail environments, exhibitions and immersive installations.

Pixel Pitch	1.953 / 2.604 / 2.976 / 3.91 mm
Refresh Rate	> 7680 Hz
Brightness	> 800 nits
Panel Size	500 x 500 x 78 mm
Viewing Angle	H160° / V140°
Life Span	100,000 Hours

Your Vision. Our Expertise. Global Impact.

Series Comparison

Model	Pitch	Density	LED	Panel Res.	Avg Power	Distance
LV-MR19	1.953 mm	262,144 pixels/sqm	SMD1415 + GOB	256 x 256 dots	< 200 W/m ²	> 1.9 m
LV-MR26	2.604 mm	147,456 pixels/sqm	SMD1415	192 x 192 dots	< 180 W/m ²	> 2.6 m
LV-MR29	2.976 mm	112,896 pixels/sqm	SMD2020	168 x 168 dots	< 200 W/m ²	> 2.9 m
LV-MR39	3.91 mm	65,536 dots/sqm	SMD2020	128 x 128 dots	< 180 W/m ²	> 3.9 m

Common Specifications

Refresh Rate	> 7680 Hz
Panel Weight	7.0 kg +/- 0.5 kg
Brightness	> 800 nits
Best Viewing Angle	H160° / V140°
Working Voltage	AC 100–240V (+/-10%)
IP Rating	Front IP20 / Rear IP20
Maintenance Way	Rear Maintenance
Max Power Consumption	< 580 W/m ²
Life Span	100,000 Hours

LV-MR19

Specification	Value
Pixel Pitch	1.953 mm
Pixel Density	262,144 pixels/sqm
Pixel Structure	SMD1415 + GOB
Module Size	500 x 250 mm
Module Resolution	256 x 128 dots
Panel Size	500 x 500 x 78 mm
Panel Resolution	256 x 256 dots
Module Arrangement	1 x 2 pcs
Average Power Consumption	< 200 W/m ²
Best Viewing Distance	> 1.9 m
Refresh Rate	> 7680 Hz
Panel Weight	7.0 kg +/- 0.5 kg
Brightness	> 800 nits
Best Viewing Angle	H160° / V140°
Working Voltage	AC 100–240V (+/-10%)
IP Rating	Front IP20 / Rear IP20
Maintenance Way	Rear Maintenance
Max Power Consumption	< 580 W/m ²
Life Span	100,000 Hours

LV-MR26

Specification	Value
Pixel Pitch	2.604 mm
Pixel Density	147,456 pixels/sqm
Pixel Structure	SMD1415
Module Size	500 x 250 mm
Module Resolution	192 x 96 dots
Panel Size	500 x 500 x 78 mm
Panel Resolution	192 x 192 dots
Module Arrangement	1 x 2 pcs
Average Power Consumption	< 180 W/m ²
Best Viewing Distance	> 2.6 m
Refresh Rate	> 7680 Hz
Panel Weight	7.0 kg +/- 0.5 kg
Brightness	> 800 nits
Best Viewing Angle	H160° / V140°
Working Voltage	AC 100–240V (+/-10%)
IP Rating	Front IP20 / Rear IP20
Maintenance Way	Rear Maintenance
Max Power Consumption	< 580 W/m ²
Life Span	100,000 Hours

LV-MR29

Specification	Value
Pixel Pitch	2.976 mm
Pixel Density	112,896 pixels/sqm
Pixel Structure	SMD2020
Module Size	500 x 250 mm
Module Resolution	168 x 84 dots
Panel Size	500 x 500 x 78 mm
Panel Resolution	168 x 168 dots
Module Arrangement	1 x 2 pcs
Average Power Consumption	< 200 W/m ²
Best Viewing Distance	> 2.9 m
Refresh Rate	> 7680 Hz
Panel Weight	7.0 kg +/- 0.5 kg
Brightness	> 800 nits
Best Viewing Angle	H160° / V140°
Working Voltage	AC 100–240V (+/-10%)
IP Rating	Front IP20 / Rear IP20
Maintenance Way	Rear Maintenance
Max Power Consumption	< 580 W/m ²
Life Span	100,000 Hours

LV-MR39

Specification	Value
Pixel Pitch	3.91 mm
Pixel Density	65,536 dots/sqm
Pixel Structure	SMD2020
Module Size	500 x 250 mm
Module Resolution	128 x 64 dots
Panel Size	500 x 500 x 78 mm
Panel Resolution	128 x 128 dots
Module Arrangement	1 x 2 pcs
Average Power Consumption	< 180 W/m ²
Best Viewing Distance	> 3.9 m
Refresh Rate	> 7680 Hz
Panel Weight	7.0 kg +/- 0.5 kg
Brightness	> 800 nits
Best Viewing Angle	H160° / V140°
Working Voltage	AC 100–240V (+/-10%)
IP Rating	Front IP20 / Rear IP20
Maintenance Way	Rear Maintenance
Max Power Consumption	< 580 W/m ²
Life Span	100,000 Hours

HGV DISPLAY

MR Series positioning is supported by Luxon Visual's current product listing. The id-33 detail page itself was unavailable to the crawler; technical values in this document use the MR-series specifications supplied in the current workflow rather than inventing unsupported values.