

				
Model	LV-DS1.5-4X1 Battery Screen	LV-DS1.8-4X1 Battery Screen	LV-DS2-4X1 Battery Screen	LV-DS2.5-4X1 Battery Screen
Pixel Pitch	1.538mm	1.86mm	2mm	2.5mm
Pixel Density	422,500pixels/sqm	288,906pixels/sqm	250,000pixels/sqm	160,000pixels/sqm
Application	Indoor	Indoor	Indoor	Indoor
LED Configuration	GOB1212	SMD1515	SMD1515	SMD1515
Module Size	320*160mm	320*160mm	320*160mm	320*160mm
Module resolution	208*104dots	172*86dots	160*80dots	128*64 dots
Shown Size	320*160mm - 4 sides	320*160mm - 4 sides	320*160mm - 4 sides	320*160mm - 4 sides
Cabinet Size	320*160mm	320*160mm	320*160mm	320*160mm
Display Resolution	416*208dots	344*172dots	320*160dots	256*128dots
Best Viewing distance	≥1.5m	≥1.8m	≥2m	≥2.5m
Brightness	600-800nits			
Refresh Rate	3840 Hz			
Best Viewing Angle	X:140° / Y:120°			
Working Voltage	AC200~240V (+/-10%)			
Maintenance Way	Front /Rear Maintence			
Power Consumption	<360W/m ²			
Life Span	100,000Hours			